



Standard Connections				
C-PTL	Size	Length	Primary	Secondary
Compac-Flange (1.4404), incl. Counter-Flange (C22.8 or 1.4404)				
SC	DN65 (40bar)	S=69,5mm	<input type="checkbox"/>	<input type="checkbox"/>
TGD	DN80 (40bar)	S=115mm	<input type="checkbox"/>	<input type="checkbox"/>
THA	DN100 (40bar)	S=142,5mm	<input type="checkbox"/>	<input type="checkbox"/>
Refrigerant-Flange (Steel), incl. Counter-Flange for Welding or Soldering				
LX	DN50 (25bar)	S=92,5mm	<input type="checkbox"/>	<input type="checkbox"/>
SX	DN65 (25bar)	S=90,5mm	<input type="checkbox"/>	<input type="checkbox"/>
TGX	DN80 (25bar)	S=104,5mm	<input type="checkbox"/>	<input type="checkbox"/>
THX	DN100 (25bar)	S=125,5mm	<input type="checkbox"/>	<input type="checkbox"/>
Solder Connections				
LZ	1 5/8" (ø 42,1mm)	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
L	2 1/8" (ø 54mm)	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
S	70,3 mm	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
LR	76,2 mm	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
LB	3 1/8" (ø79,2mm)	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
TN	4 1/8" (ø105mm)	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
Additional Connections on the Backplate (Internal Thread)				
OZ	G 1/2	S=27,5mm	<input type="checkbox"/>	<input type="checkbox"/>
Other Connections on Inquiry!				

No. of Plates	50	60	70	80	90	100	110	120	130	140	150
Weight Empty (kg)	102,0	114,5	127,0	139,5	152,0	164,5	177,0	189,5	202,0	214,5	227,0
Surface (m <sup>2</sup> )	14,4	17,4	20,4	23,4	26,4	29,4	32,4	35,4	38,4	41,4	44,4
No. of Plates	160	170	180	190	200	210	220	230	240	250	260
Weight Empty (kg)	239,5	252,0	264,5	277,0	289,5	302,0	314,5	327,0	339,5	352,0	364,5
Surface (m <sup>2</sup> )	47,4	50,4	53,4	56,4	59,4	62,4	65,4	68,4	71,4	74,4	77,4
No. of Plates	270	280	290	300							
Weight Empty (kg)	377,0	389,5	402,0	414,5							
Surface (m <sup>2</sup> )	80,4	83,4	86,4	89,4							

$L=23,0+2,35xN$

GEA WTT - Plate Heat Exchanger Type 10			Operating-	
Model	Stainless Steel	Solder	Temperature	Pressure
<input checked="" type="checkbox"/> WP10-...	1.4404	Copper	± 195°C	30 bar
<input type="checkbox"/> WP10L-...	1.4404	Copper	± 195°C	25 bar

**GEA WTT GmbH**

Firmenname  
GEA WTT GmbH  
Remsaer Str. 2a  
04603 Nobitz - Wilchwitz Germany  
Phone:+49(0)3447-5539-0/Fax:+49(0)3447-5539-30  
www.geawtt.com / www.gea-ecobraze.se  
sales@geawtt.com / info@gea-ecobraze.se

Zeichnungsname, Benennung, Werkstoff, Abmessungen usw			Rohteil-, Modell-, Werkst.Nr.	
Gezeichnet	Geprüft	Genehmigt - datum	Datum	Maßstab
Graichen			10.01.2005	1:7,5
Zeichnungsnummer				Blatt
10-0501.0508.02-E				

The manufacturer herewith certifies that construction, production and examination of his pressure vessel are in conformity with EU guideline 97/23/EC.